

Compact Utility Range

4025 (41HP) /
3650 (50HP)

 **#1**
SELLING
TRACTOR

4.5 MILLION+
TRACTORS SOLD
GL  BALLY

SOLD IN **50+**
COUNTRIES



mahindra *Rise*

3650 PST SUPERIOR PERFORMANCE

HIGHLY COMFORTABLE OPERATOR ENVIRONMENT

These tractors come standard with a list of deluxe features that offer supreme comfort and ease of operation to the operator. The fully flat operator deck is covered with a rubber mat, side shift gear controls and the suspended brake and clutch pedals provide lots of legroom and a roomy work area. The deluxe seat features wide formed cushions, adjustable suspension and armrests. Coupled with the tiltable steering column, the operator can select the best suited driving position, just what's needed for those long hauls.

HEAVY DUTY FRONT AXLE

The heavy-duty front axle ensures maximum reliability in loader and field operations. The bevel gear front axle with a responsive hydrostatic steering provides a tight steering angle, so getting in and out of confine areas is easy.



4025 2WD (41HP)

This economical, rugged utility tractor now offers versatility and ergonomic comfort. Its simplicity and tough-terrain durability make it the perfect high value tractor for everything from material handling, lifting and digging to rotary-cutting and graining.



4025 4WD (41HP)

The Mahindra 4025 is one of the heaviest with an overall weight of 2360 kgs and is the most rugged tractors in its category. It has a large capacity engine, heavy duty transmission, high lift capacity hydraulics and very robust cast iron chassis.



Loader Specifications

Maximum Lift Height	2772 MM
Clearance With Attachment Level	2484 MM
Clearance With Attachment Dumped	1956 MM
Reach At Maximum Height	556 MM
Maximum Dump Angle	60°
Digging Depth Below Grade	180 MM
Overall Height In Carry Position	1550 MM
Depth Of Attachment (to Back Of Inner Shell)	591 MM
Height Of Attachment	581 MM
Depth Of Attachment (to Pivot Pin)	801 MM
Lift Capacity To Full Height At Pivot Pins	1089 KGF
Safe Working Load	700 KGS WITH BALLAST
Breakout Force At Ground Level, Pivot Pins	2364 KGF
Relief Valve Setting (loader Control Valve)	180 KG/CM2
Attachment Width Used For Specification	1650 MM
Bucket Capacity	0.33 CU.M
Bucket Level Indicator	STANDARD
Optional Attachments (for All Models)	GRILL GUARD, BALE SPIKES, PALLET FORKS

Self Level Mechanism	Yes
Maximum Lift Height	2610 mm
Clearance Attachment Level	2396 mm
Clearance Bucket Dumped	1859 mm
Reach at Maximum Height	354 mm
Maximum Dump Angle	58°
Reach with Attachment on Ground	1595mm
Attachment Rollback Angle	36°
Digging Depth Below Grade	80 mm
Overall Height Carry Position	1627 mm
Depth of Attachment (to back of inner shell)	591 mm
Height Attachment	544 mm
Length Attachment (to pivot pin)	768 mm
Lift Capacity Full Height Pivot Pins	1310 kgf
Breakout Force Ground Level, Pivot Pins	2173 kgf
Relief Valve Setting (Loader Control Valve)	180 kg/cm2
Attachment Used for Specification	1520 mm
Bucket Capacity	0.274 cu.m
Hydraulic System	Tractor pump with loader control valve
Bucket Level indicator	Standard
Optional Attachments	Grill guard



Proven Quality - Japan Quality Medal Winner

Quality is paramount at Mahindra and we are proud to be the first and only tractor manufacturing company in the world to win the Japan Quality Medal (JQM), a laurel truly hard to earn. It is universally acclaimed as the highest award presented to a company following Total Quality Management (TQM) practices in their entire business operations. JQM recognizes a high level of customer focus, improvements in overall quality and excellence in business processes.

REAR ATTACHMENTS



1. Grader Blade

2. Log Splitter

3. Landscape Rake

4. Fertiliser Spreader

5. Offset Disc

6. Post Hole Digger

7. Box Blade

8. Ballast Box

9. Carry All

10. 3 Point Linkage Bale Spike

11. 1.2m (4ft) Slasher/Rotary Cutter

12. Rear Finishing Mowers for finished lawn

Rear Attachments available through your Local Mahindra Dealer

Specifications

ENGINE	4025 2WD	4025 4WD	3650 PST
Compression Ratio	19:5:1	19:5:1	18:5:1
Emission	Tier 4 Compliance (Interim)	Tier 4 Compliance (Interim)	-
Cylinders	4	4	4
Cylinder Sleeve	Wet replaceable	Wet replaceable	-
Displacement	2732 cc	2732 cc	2731 cc
Max Engine Hp (kw) @ Rpm	41 (30.5) @ 2300	41 (30.5) @ 2300	49 HP (36.5) @ 2800 RPM
Type	Four Stroke, Direct Injection, Watercooled, Diesel	Four Stroke, Direct Injection, Watercooled, Diesel	Naturally Aspirated, Direct Injection, Diesel Engine
ELECTRICAL			
Battery Capacity	12 volt, 88 amp hours	12 volt, 88 amp hours	12 volt, 96 amp hours
Alternator	12 volt, 36 amps	12 volt, 36 amps	12 volt, 45 amps
CLUTCH			
Type	Dual	Dual	Wet Multidisc
TRANSMISSION			
Type	Sliding mesh	Full Constant mesh	Power Shuttle
Number Of Gears/Speeds	8F / 2R	8F / 2R	12 Forward / 12 Reverse
FRONT WHEEL DRIVE			
Type	-	Mechanical Engagement	Mechanical Engagement
STEERING			
Type	Hydrostatic power	Hydrostatic power	Hydrostatic power
Pump Output (l/min)	18.9	18.9	18.9
BRAKES			
Type	Fully enclosed dry disc	Fully enclosed dry disc	Wet Disc
HYDRAULIC SYSTEM			
3-point Linkage	Category 1 & 2	Category 1 & 2	Category I & II, W/ Telescopic Lower Link And Stabiliser
Auxiliary Remote Valves	1 spool optional	1 spool optional	Single Spool Double Acting
Lift Capacity	1600	1600	1402 Kgs
Pump Output (l/min)	33	33	41.6
Type	Open centre, full-live hydraulic with position and draft controls	Open centre, full-live hydraulic with position and draft controls	Open Centre, Full-live Hydraulic With Position And Draft Controls
PTO			
Max PTO HP (kw)	31 (23.1)	31 (23.1)	41 (30.7)
PTO Rpm @ Engine Rpm	540 @ 2058	540 @ 2058	540
Type	Rear, 6 Spline, Single Speed, CRPTO	Rear, 6 Spline, Single Speed, CRPTO	Independent With Electro - Hyrdualic Engagement
OPERATING WEIGHT			
Total	1990 kgs	2360 kgs	2200 kgs
DIMENSIONS			
Overall Length	2928 mm	3290 mm	3274 mm
Overall Width	1762 mm	2090 mm	1915 mm
Turning Radius	2900 mm	6400 mm	3150 mm
WHEELS & TYRES			
Standard Ag (Front/Rear)	6 X 16 / 12.4 X 28 (Standard)	-	9.5 X 20 / 16.9 X 24 (Standard)
Optional Ag (Front/Rear)	-	9.5 X 16 / 12.4 X 28	-
Optional Industrial (Front/Rear)	-	12 X 16.5 / 16.9 X 24 (Standard)	14 x 17.5 / 19.5 x 24

Photographs may show overseas models or illustrate non-standard equipment. Please read your Mahindra Tractor manual carefully prior to operation. ^3 Year Engine & Powertrain warranty. #Mahindra & Mahindra Ltd is the No.1 Tractor company in the world by volume. Information subject to change without notice.

Mahindra Ag and Auto Australia



4/20 Buttonwood Place, Willawong
Brisbane QLD 4110 Australia.
Phone: (07) 3213 1211,
Email: info@mahindra.com.au
www.mahindraag.com.au



Dealer Details: